

SPH 3000-6000TL-HUB

All-In-One Energy Storage Solution

- Easy installation with modular design
- Faster energy store with 0.75C battery charge power
- Smart bypass function ensures continues critical loads
- Max. 16A PV input per string
- Type II/III SPD on DC/AC side
- VPP interface ready



P O W E R
- I N G O
T O M O -
R R O W O

System Parameters

System schematic								
Battery model	ALP 5.0L-E1							
Battery type	LiFePO4							
Number of inverter module	1							
Number of battery module	1	2	3	4	5	6	7	8
Energy capacity	5kWh	10kWh	15kWh	20kWh	25kWh	30kWh	35kWh	40kWh
Weight	80kg	125kg	170kg	215kg	260kg	305kg	350kg	395kg
Dimension (W/D/H)	690/186/1102mm	690/186/1397mm	690/186/1692mm	690/186/1987mm	690/186/1692mm 690/186/705mm	690/186/1692mm 690/186/1000mm	690/186/1692mm 690/186/1295mm	690/186/1987mm 690/186/1295mm
Inverter Module	SPH 3000TL-HUB	SPH 3600TL-HUB	SPH 4000TL-HUB	SPH 4600TL-HUB	SPH 5000TL-HUB	SPH 6000TL-HUB		
Input Data (PV)								
Max. recommended PV power (for module STC)	6000W	7200W	8000W	9200W	10000W	12000W		
Max. DC voltage	600V							
Start voltage	100V							
Nominal voltage	370V							
MPP work voltage range	100V~560V							
No. of MPP trackers	2							
No. of PV strings per MPP tracker	1							
Max. input current per MPP tracker	16A							
Max. short-circuit current per MPP tracker	24A							
Output/Input Data (AC)								
AC nominal power	3000W	3680W	4000W	4600W	5000W	6000W		
Rated AC apparent power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA		
Nominal AC voltage/range	230V ; 180Vac-260Vac							
Nominal frequency/range	50/60Hz; 45~55Hz/55~65Hz							
Rated input/output current	13A/13A	16A/16A	17.3A/17.3A	20A/20A	21.7A/21.7A	26A/26A		
Max. input/output current	16/16A	16/16A	22/22A	22/22A	27/27A	27/27A		
Adjustable power factor	0.8leading...0.8lagging							
THDi	<3%							
AC connection	Single phase							
Backup Power(AC)								
Rated output apparent power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA		
Nominal voltage	230V							
Nominal frequency	50/60Hz							
Rated output current	13A	16A	17.3A	20A	21.7A	26A		
THDv	3%							
Switch time	≤15ms							
Efficiency								
Max. efficiency	97.20%	97.20%	97.30%	97.40%	97.50%	97.60%		
MPPPT efficiency	≥99.5%	≥99.5%	≥99.5%	≥99.5%	≥99.5%	≥99.5%		
Battery Data (DC)								
Battery module	ALP 5.0L-E1							
Normal voltage	51.2V							
Number of battery modules	1~8							
Energy capacity	5~40kWh							
Max. discharge/charge rate	0.75C							
DoD	92%							
Dimensions (W/D/H)	690/185/295mm							
General Data								
Operating temperature range	0°C ... +45°C							
DC/AC surge protection	Type II/III							
Altitude	3000m							
Self-Consumption	< 10 W							
Cooling	Natural							
Relative humidity	5~95%							
Protection degree	IP66							
PV connection	MC4							
AC connection	Connector							
Battery connection	Quick Terminal							
Installation method	Floor/Wall mount							
Display	LCD							
Warranty	10 years							
Interfaces	RS485/USB/CAN/Wi-Fi/GPRS							
Country of manufacturing	Made in China							

CE, IEC62109, IEC61000, AS4777.2:2020, CEC

* The maximum working voltage is 560V, and if it exceeds 560V, the system will not work or stop working; The maximum input voltage is 600V, there is a risk of damage if the maximum value is exceeded.

* Due to the limitation of battery discharge current, if there is only one pack, the maximum discharge power of the inverter is only 3.8kw. If the discharge power needs to reach >4kw, the minimum capacity configuration requires two packs.*

* SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. Subject to change without notice.

SHENZHEN GROWATT NEW ENERGY CO.,LTD. A: 4-13/F, Building A, Sino-German(Europe) Industrial Park, Hangcheng Ave, Bao'an District, Shenzhen, China
T: +86 755 2747 1900 F: +86 755 2749 1460 E: info@ginverter.com